



100% Material Declaration Data Sheet FS48

PK150 (v1.2) September 29, 2006

Material Declaration Data Sheet

Average Weight: 0.1 g

Component	Substance Description	CAS# or Description	% of Component	Use in Product	Component Weight/ Substance Weight (in grams)	Component % of Total
Silicon Die					0.0059	5.90 %
	Silicon	7440-21-3	100.00		0.0059	
Die Attach Material					0.00205	2.05%
	Silver	7440-22-4	75.00	Filler	0.0015375	
	Epoxy Resin	29690-82-2	25.00		0.0005125	
Encapsulant					0.04265	42.65 %
	Epoxy	29690-82-2	26.50		0.01130225	
	Carbon Black	1333-86-4	0.50		0.00021325	
	Silica	60676-86-0	70.00		0.029855	
	Antimony Trioxide	1309-64-4	2.00		0.000853	
	Brominated Flame Retardant (TBBA)	79-94-7	1.00	Flame Retardant	0.0004265	
Laminate					0.03525	35.25 %
	Bismaleimide/Triazine Board	13676-54-5/25722-66-1	69.00		0.0243225	
	Copper	7440-50-8	20.00	Metal Layer	0.00705	
	Nickel	7440-02-0	0.80	Metal Layer	0.000282	
	Gold	7440-57-5	0.20	Metal Layer	0.0000705	
	Resist	Trade Secret	9.00		0.0031725	
	Brominated Flame Retardant (TBBA)	79-94-7	1.00	Flame Retardant	0.0003525	
Bond Wire					0.00095	0.95%
	Gold	7440-57-5	100.00		0.00095	
Solder Balls					0.0132	13.20 %
	Tin	7440-31-5	63.00		0.008316	
	Lead	7439-92-1	37.00		0.004884	

PK150 (v1.2) September 29, 2006

www.xilinx.com

1

Revision History

The following table shows the revision history for this document.

Date	Revision	Revision
4/06/06	1.0	Initial release.
7/28/06	1.1	100% Material Declaration.
9/29/06	1.2	Updated component descriptions.