



PK209 (v1.1) January 16,
2012

100% Material Declaration Data Sheet SO20

Average Weight: 0.5610 g

Component	Substance Description	CAS# or Description	% of Component	Use in Product	Component Weight/ Substance Weight (in grams)	Component % of Total
Silicon Die					0.019350	3.450
	Silicon	7440-21-3	100.00		0.019350	
Die Attach Material					0.003350	0.597
	Resin	Trade Secret	21.00		0.000703	
	Silver (Ag)	7440-22-4	70.00		0.002342	
	Metal oxide	Trade Secret	3.00		0.000100	
	Amine	Trade Secret	3.00		0.000100	
	Gamma Butyrolactone	Trade Secret	3.00		0.000100	
Mold Compound					0.369890	65.930
	Silica Fused	60676-86-0	86.00		0.296778	
	Epoxy Resin (EP)	Trade Secret	7.50		0.027741	
	Carbon Black	Trade Secret	0.50		0.001849	
	Epoxy Cresol Novolac	29690-82-2	2.00		0.007398	
	Phenol Resin	Trade Secret	4.00		0.014795	
Lead Frame					0.161900	28.860
	Copper	7440-50-8	97.50		0.157854	
	Iron	7439-89-6	2.35		0.003805	
	Phosphorus	7723-14-0	0.03		0.000049	
	Zinc	7740-66-6	0.12		0.000194	
Lead Frame Plating					0.001740	0.310
	Silver (Ag)	7440-22-4	100.00		0.001740	
Gold Wire					0.000770	0.137
	Gold (Au)	7440-57-5	100.00		0.000770	
External Plating					0.004000	0.658
	Tin (Sn)	7440-31-5	85.00		0.003400	
	Lead (Pb)	7439-92-1	15.00		0.000600	

Revision History

The following table shows the revision history for this document.

Date	Version	Description of Revisions
10/05/06	1.0	Initial Xilinx release.
01/16/12	1.1	CAS# Update.

Notice of Disclaimer

Xilinx regards this materials data to be correct but makes no guarantee as to its accuracy or completeness, including, but not limited to, with respect to its compliance with applicable environmental laws and regulations. Xilinx subcontracts the production, test and assembly of hardware devices to independent third-party vendors and materials suppliers (“Contractors”). All data provided hereunder is based on information received from Contractors. Xilinx has not independently verified the accuracy or completeness of this information which is provided solely for your reference in connection with the use of Xilinx products.