



PK584 (v1.0) September 28,  
2012

# 100% Material Declaration Data Sheet FG400 XC3S400AN

**Average Weight: 2.0455 g**

Component	Substance Description	CAS# or Description	% of Component	Use in Product	Component Weight/ Substance Weight (in grams)	Component % of Total
<b>Silicon Die (FPGA)</b>					<b>0.017871</b>	<b>0.874</b>
	Silicon (Si)	7440-21-3	100.00		0.017871	
<b>Silicon Die (PROM)</b>					<b>0.002099</b>	<b>0.103</b>
	Silicon (Si)	7440-21-3	100.00		0.002099	
<b>Die attach</b>					<b>0.002719</b>	<b>0.133</b>
	Silver	7440-22-4	77.50		0.002107	
	Bismaleimide Monomer	Trade Secret	15.00		0.000408	
	Acrylate Monomer	Trade Secret	7.50		0.000204	
<b>Film</b>					<b>0.000010</b>	<b>0.000</b>
	Epoxy Resin	N/A	12.50		0.000001	
	Phenol Resin	N/A	12.50		0.000001	
	Amorphous Silica	7631-86-9	35.00		0.000004	
	Synthetic Rubber	N/A	40.00		0.000004	
<b>Mold Compound</b>					<b>0.824233</b>	<b>40.296</b>
	Silica Fused	60676-86-0	70.90		0.584381	
	Silica Fused	7631-86-9	15.00		0.123635	
	Silica, Crystalline	14808-60-7	0.30		0.002473	
	Epoxy resin A	Trade Secret	3.00		0.024727	
	Epoxy resin B	Trade Secret	3.00		0.024727	
	Phenol resin A	Trade Secret	3.00		0.024727	
	Phenol resin B	Trade Secret	3.00		0.024727	
	Metal Hydroxide	Trade Secret	1.50		0.012363	
	Carbon Black	1333-86-4	0.30		0.002473	
<b>Solder Ball</b>					<b>0.380719</b>	<b>18.613</b>
	Tin	7440-31-5	63.00		0.239853	
	Lead	7439-92-1	37.00		0.140866	

**100% Material Declaration Data Sheet – FG400 XC3S400AN**

Component	Substance Description	CAS# or Description	% of Component	Use in Product	Component Weight/ Substance Weight (in grams)	Component % of Total
<b>Gold Wire 1</b>					<b>0.016172</b>	<b>0.791</b>
	Gold	7440-57-5	99.05		0.016018	
	Palladium	7440-05-3	0.95		0.000154	
	Calcium	7440-70-2	0.00		0.000000	
<b>Gold Wire 2</b>					<b>0.000546</b>	<b>0.027</b>
	Gold	7440-57-5	99.05		0.000541	
	Palladium	7440-05-3	0.95		0.000005	
	Calcium	7440-70-2	0.00		0.000000	
<b>Substrate</b>					<b>0.801090</b>	<b>39.164</b>
	Copper	7440-50-8	35.78		0.286630	
	Nickel	7440-02-0	3.98		0.031883	
	Gold	7440-57-5	0.48		0.003845	
	Glass fiber	65997-17-3	16.69		0.133702	
	Halogen FR	N/A	0.10		0.000801	
	BT Core	13676-54-5 25722-66-1 29690-82-2 26265-08-7 13776-74-4 7631-86-9 7440-50-8	34.25		0.274373	
	Solder mask	64742-94-5 14807-96-6 7727-43-7 7631-86-9 34590-94-8	8.72		0.069855	

## Revision History

The following table shows the revision history for this document.

Date	Version	Description of Revisions
09/28/12	1.0	Initial Xilinx release.

---

## Notice of Disclaimer

Xilinx regards this materials data to be correct but makes no guarantee as to its accuracy or completeness, including, but not limited to, with respect to its compliance with applicable environmental laws and regulations. Xilinx subcontracts the production, test and assembly of hardware devices to independent third-party vendors and materials suppliers (“Contractors”). All data provided hereunder is based on information received from Contractors. Xilinx has not independently verified the accuracy or completeness of this information which is provided solely for your reference in connection with the use of Xilinx products.